

Please type a plus sign (+) inside this box → ☐

Approved for use through 09/30/2000. OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))

Attorney Docket No. 5932.1
First Inventor or Application Identifier Douglas W. King
Title Method of and System for Making Purchases Over a Computer Network
Express Mail Label No. EL317433794US

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

1. ☒ * Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original and a duplicate for fee processing)
2. ☒ Specification [Total Pages 16]
(preferred arrangement set forth below)
 - Descriptive title of the invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to Microfiche Appendix
 - Background of the invention
 - Brief Summary of the invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
3. ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets 14]
4. Oath or Declaration [Total Pages 2]
 - a. ☒ Newly executed (original or copy)
 - b. ☐ Copy from a prior application (37 C.F.R. § 1.63(d))
(for continuation/divisional with Box 16 completed)
 - i. ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).

* NOTE FOR ITEMS 1 & 13: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28).

ADDRESS TO:

Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

5. ☐ Microfiche Computer Program (Appendix)
6. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
 - a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

7. ☐ Assignment Papers (cover sheet & document(s))
8. ☐ 37 C.F.R. § 3.73(b) Statement (when there is an assignee) ☒ Power of Attorney
9. ☐ English Translation Document (if applicable)
10. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
11. ☐ Preliminary Amendment
12. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
13. ☐ * Small Entity Statement(s) ☐ Statement filed in prior application, Status still proper and desired (PTO/SB/09-12)
14. ☐ Certified Copy of Priority Document(s) (if foreign priority is claimed)
15. ☐ Other: _____

16. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No: _____
Prior application information: Examiner _____ Group / Art Unit: _____

For CONTINUATION or DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

17. CORRESPONDENCE ADDRESS

☐ Customer Number or Bar Code Label ☒ Correspondence address below
(Insert Customer No. or Attach bar code label here)

Name James E. Marina, Esq.
Address Winston & Strawn
200 Park Avenue
City New York State NY Zip Code 10166
Country U.S.A. Telephone 212-294-6700 Fax 212-294-4700

Name (Print/Type) James E. Marina Registration No. (Attorney/Agent) 41,969
Signature [Signature] Date 9/7/99

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231

TITLE OF THE INVENTION

Method of and System for Making Purchases Over a Computer Network

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention generally relates to a method of and system for making purchases over a computer network and, more particularly, to a method of and system for making purchases of goods and services over the Internet or other non-secure computer network using an automated-teller-machine (ATM) card, debit card or any other card which may require a valid personal-identification-number (PIN) for transaction authorization.

2. Description of the Prior Art

The use of personal computers by consumers to purchase goods and services over the Internet via the World Wide Web and e-mail has become very popular in recent years and constitutes an ever-increasing part of the economy. In making a purchase over the Internet, the typical consumer uses a credit card or ATM card. After making his purchase selection, the consumer transmits his card information over the Internet to the on-line merchant. The on-line merchant then contacts the issuing bank to verify the card information and obtain authorization to complete the transaction. Depending on the response from the bank, the on-line merchant either accepts or rejects the purchase.

Because the Internet is a non-secure (i.e., public) network, there is a danger that the consumer's credit card or ATM card information will be intercepted by a third party. If that third party is dishonest, he can make illegal charges to the credit card or, in the case of an

ATM card, remove money directly from the consumer's bank account. In recent years, numerous approaches have been implemented to reduce this security risk. The most popular approach has been sophisticated encryption techniques which render the credit card or ATM card data virtually unreadable to third parties, such as 128-bit secure-sockets-layer (SSL) encryption.

When making purchases over the Internet using an ATM card, however, security considerations take on an added importance because, unlike with transactions at ATM machines, PINs are presently not used in ATM transactions on the Internet. Thus, should the ATM card number fall into the hands of an unscrupulous third party, the card-holder's entire bank account can be wiped out through fraudulent Internet transactions.

One way to overcome this problem is to require the use of PINs in ATM transactions on the Internet. This has not been possible to date, however, because on-line merchants do not have the ability to verify PINs. Additionally, it is not desirable to provide the on-line merchant with both the ATM card number and the corresponding PIN since unscrupulous employees of the on-line merchant can use the PIN to illegally access the card-holder's bank account and withdraw money therefrom.

Accordingly, it is an object of the present invention to provide a new method of and system for making purchases over the Internet using an ATM card wherein a valid PIN is required in order to obtain authorization for a given transaction. It is another object of the present invention to provide a new method of and system for making purchases over the Internet using an ATM card wherein a valid PIN is required in order to obtain authorization for a given transaction, and wherein the PIN is not supplied to the on-line merchant.

SUMMARY OF THE INVENTION

In accordance with a first aspect of the present invention, a method of making purchases over a non-secure computer network using an ATM card is provided. In accordance with said method, a consumer transmits his ATM card number over the network to an on-line merchant. The on-line merchant then forwards the ATM card number to a third party contractor, such as a bank, that will oversee and authorize the transaction.

Simultaneously or thereafter, the consumer transmits his PIN over the network to the third party contractor, bypassing the on-line merchant. Having both the ATM card number and the PIN, the third party contractor verifies that the ATM card number and PIN are correct, checks for sufficiency of funds, and either authorizes or denies the transaction. The authorization or denial is communicated to the on-line merchant over the network, who either completes or rejects the purchase and so notifies the consumer.

In accordance with a second aspect of the present invention, a system for making purchases over a non-secure computer network using an ATM card is provided. The system includes first, second and third computers connected to a computer network. The first computer transmits the consumer's ATM card number over the network to the second computer, which is operated by or for the on-line merchant. The second computer forwards the ATM card number over the network to the third computer, which is operated by or for the third party contractor. Simultaneously or thereafter, the first computer transmits the consumer's PIN over the network to the third computer, bypassing the second computer. The third computer then verifies that the ATM card number and PIN are correct and that there are sufficient funds in the bank account to cover the transaction amount. The third computer then transmits the results of the verification procedure to the second computer, which

forwards the results to the first computer. Depending on the verification results, the purchase is either completed or rejected.

The present invention will now be described in detail, with frequent reference being made to the drawings identified below.

5

BRIEF DESCRIPTION OF THE DRAWINGS

In the accompanying drawings:

figure 1 is a schematic diagram of the system in accordance with the present invention;

10 figure 2 is a flow chart which illustrates how the system of figure 1 operates;

figure 3 shows a possible graphical user interface which can be used to enable the consumer to enter and transmit his PIN to the third party contractor;

figure 4 is a diagram which summarizes the present invention;

15 figures 5(a) - (d) show a computer program which can be used to format the data package sent from the second computer to the third computer in ISO 8583 format; and

figures 6(a) - (f) show a computer program which can be used by the third computer to synchronize the data packages received from the first and second computers.

DESCRIPTION OF THE PREFERRED EMBODIMENT

20 The system 10 in accordance with the present invention is schematically shown in figure 1. The system 10 includes a first computer 12 at a consumer location 14, a second computer 16 at an on-line merchant location 18, and a third computer 20 at a third party contractor location 22. The three computers 12, 16, 20 are connected together over a

computer network 24 which, for purposes of this discussion, is the Internet, although the present invention may be practiced on any computer network. As those of ordinary skill in the art know, the Internet 24 is a complex and amorphous computer network that comprises thousands of nodes and components and over which signals are transmitted by telephone lines, satellites and optical fibers.

The first computer 12, which will generally be located at the consumer's home or business (consumer location 14), will typically be a conventional personal computer (PC) that includes a chassis that houses a central processing unit (CPU) and supporting circuitry, as well as a floppy drive, a hard drive and an internal modem. Connected to the CPU through the chassis are a keyboard, a mouse and a monitor. The keyboard and mouse are used by the consumer to control the operation of the first computer 12 and to input information into the first computer 12. The first computer 12 will usually be coupled to the Internet via a telephone line connected to the modem, although the computer can be connected to the Internet via a high speed data transmission line. The consumer will typically connect to the Internet using an Internet service provider, such as Erols™ or America OnLine™, but may have a direct connection to the Internet.

Although a conventional PC will typically be used by the consumer, the consumer may use any type of computer that can be connected to the Internet, including a work station on a local area network, and any operating system. The particular details of the first computer 12 are largely irrelevant to the present invention. The first computer 12 merely serves as a convenient interface for the consumer to place orders for goods and services over the Internet.

Next shown in figure 1 is the second computer 16 which is located at the on-line merchant location 18. The second computer 16 will preferably be a more powerful machine than a personal computer, such as a workstation, although a personal computer may also be used by the on-line merchant. Again, the particular details of the second computer 16 are
5 largely irrelevant to the present invention.

Typically, the second computer 16 will be a Web server (a computer that provides direct access to the World Wide Web on the Internet and includes the necessary hardware, operating system, Web server software, TCP/IP protocols and Web site content) owned and operated by the on-line merchant or by an Internet service provider with whom the on-line
10 merchant has contracted. For purposes of this discussion, the on-line merchant location 18 refers to the location of the second computer 16, and not necessarily the actual physical location of the on-line merchant.

Preferably, the second computer 16 will be running Windows NT™ 4.0, using Internet Information Server™ 4.0 and Commerce Server™ 3.0. The CPU of the second
15 computer 16 must have acceptable power and should have at least 64 megabytes of RAM.

The second computer 16 will typically have an on-line catalog in memory which can be accessed and browsed by the consumer over the Internet 24 through an appropriate graphical use interface (GUI) supplied by the on-line merchant.

Next shown in figure 1 is the third computer 20 which is located at the third party
20 contractor location 22. The third party contractor is an independent, insured organization, such as a bank, that has contracted with the on-line merchant to provide ATM services. Although the third computer 20 can be a personal computer, as with the second computer 16 it will preferably be a much more powerful machine, such as a workstation. The third

computer 20 is likewise preferably a Web server owned and operated by the third party contractor or by an Internet service provider with whom the third party contractor has contracted. The third party contractor location 22 refers to the location of the third computer 20 and not necessarily the actual physical location of the third party contractor. As with the first and second computers 12, 16, the particular details of the third computer 20 are largely irrelevant to the present invention, so long as the third computer 20 is capable of performing the functions described herein. Preferably, the third computer is Compaq ProLiant™ server running at 500 MHZ with 128 MB RAM and using Windows NT™ 4.0.

The flow chart 26 provided in figure 2 illustrates how the system 10 operates. As shown in block 28, the consumer initially establishes a connection over the Internet between the first computer 12 and the second computer 16 by accessing the on-line merchant's Web site using a commercially available browser, such as Internet Explorer™ or Netscape Navigator™. Then, as shown in blocks 30 and 32, using a GUI supplied by the on-line merchant, the consumer browses the on-line catalog, selecting which goods and/or services he wishes to purchase. Once the consumer makes his selection and is ready to place an order, the consumer transmits a purchase order message over the Internet to the on-line merchant (block 34).

The consumer is then prompted for his payment information, as indicated in block 36, which for purposes of the present discussion is an ATM card number and expiration date, although the payment information can include additional data such as the consumer's name and address. The consumer then transmits his payment information over the Internet to the on-line merchant, as indicated in block 38. As used herein, the term "ATM card" includes bank cards, debit cards and any other cards for which the issuing bank or organization may

require a valid PIN for use. The payment information is transmitted over the Internet using an encrypted connection, such as 128-bit encryption SSL.

When the on-line merchant receives the ATM card number, or earlier, the second computer 16 creates a unique session identifier by combining the consumer's IP address, which uniquely identifies the consumer, with a date/time stamp. The ATM card number is then forwarded, or echoed, over the Internet by the second computer 16 to the third computer 20 at the third party contractor location 22 (block 40), along with the unique session identifier, a merchant id which uniquely identifies the on-line merchant, a terminal id which identifies the terminal being used by the on-line merchant, the expiration date of the ATM card and the purchase price. This data package is stored in memory on the third computer in a queue. Once again, 128-bit encryption SSL is preferably used.

The data package transmitted by the second computer 16 to the third computer 20 is transmitted in ISO 8583 format. ISO 8583 is a messaging standard established by the International Standards Organization for financial transaction card oriented messages which is used by all banks and credit card companies and which is well known to those of ordinary skill in the art. A sample computer program written in Java which creates the unique session identifier and formats the data package in ISO 8583 format is provided in figure 5. This program is designed to run as an Active Server Page on Internet Server 4.0 under Windows NT 4.0, although the program can be used on other platforms and programming environments, and can readily be implemented by one of ordinary skill in the art.

Simultaneously or soon thereafter, the second computer executes a hyperlink to the third computer and the consumer is prompted by the third computer to input his PIN (block 42). The consumer inputs his PIN into the first computer 12 and transmits it over the Internet

to the third computer 20 (block 44). The connection between the first computer 12 and third computer 20 is encrypted and independent of the connection between the first computer 12 and the second computer 16 so that the on-line merchant is never in possession of the PIN. As with the second computer 16, the first computer 12 transmits the unique session identifier, the merchant id, the terminal id, the expiration date of the ATM card and the purchase price to the third computer 20 along with the PIN in a data package.

Figure 3 shows a typical GUI 46 which may be supplied by the third-party contractor and which pops up on the consumer's screen to allow the consumer to enter his PIN and transmit it to the third party contractor. As is clear from figure 3, the GUI 46 emulates an actual ATM machine and includes a simulated key pad 48 and a screen 50. The screen 50 indicates the on-line merchant's name and mailing address 52 and the purchase price 54. Using his mouse, the consumer inputs his PIN, as shown by the series of dots 56. By pressing the SUBMIT button 58, the PIN number is transmitted to the third party contractor. If the consumer makes a mistake, he presses the CLEAR button 60 and re-types his PIN. If the consumer needs help from the third party contractor, he simply presses the HELP button 62, which causes a help menu provided by the third party contractor to pop up on the screen, which may then be navigated by the consumer.

The third computer 20 next verifies that the ATM card number and PIN are valid (block 64). Because the third-party contractor may be overseeing multiple transactions at any given time, the third computer 20 must synchronize the data packages received from the first and second computers 12, 16. To do this, the third computer 20 matches the unique session identifier, the merchant id, the terminal id, the expiration date of the ATM card and the purchase price fields contained in the data packages received from the first and second

computers 12, 16. A sample computer program for synchronizing the messages received from the first and second computers 12, 16 is provided in figure 6. The program is written in C++ and can readily be implemented by one of ordinary skill in the art. All of the forgoing data fields must match in order for the transaction to take place. For security reasons, a two
5 minute window for matching is preferably implemented. If there is no match within the two minute window, the transaction is aborted.

Once the data packages from the first and second computers 12, 16 are synchronized by the third computer 20, the third computer checks the ATM card number and PIN. If the ATM card number and PIN are invalid, the third computer 20 so informs the second
10 computer 16 and the on-line merchant rejects the purchase order and notifies the consumer (block 66). If the ATM card number and PIN are valid, the third computer 20 checks to see whether there are sufficient funds to cover the purchase price 56 (block 68). If there are sufficient funds in the account, the third computer transmits an authorization message to the second computer, debits the consumer's account, the purchase is completed and the consumer
15 is notified (block 70). If there are insufficient funds, a rejection message is transmitted, the on-line merchant rejects the purchase and the consumer is notified (block 72).

If the ATM card was issued by the third party contractor, the verification steps (blocks 64 and 68) may be done by simply accessing an internal database in or connected to the third computer 20. If, however, the ATM card was issued by another bank, then the third
20 party contractor must verify the card information by contacting the issuing bank, either directly over a secure line, through a private ATM network, such as CIRRUS, or through any other available avenue.

The present invention is briefly and concisely summarized in figure 4. First, the consumer (first computer) transmits his ATM card number over the network to the on-line merchant (second computer) (block 74). Second, the on-line merchant forwards the ATM card number over the network to the third party contractor (third computer) (block 76).

5 Third, the consumer transmits his PIN over the network to the third party contractor (block 78). As figure 4 indicates, the on-line merchant is completely bypassed and never receives the PIN. Fourth, the third party contractor verifies the ATM card number and PIN and checks for sufficiency of funds (block 80). Fifth, the third party contractor transmits the results of the verification process over the network to the on-line merchant (block 82). And
10 sixth, the on-line merchant forwards the results over the network to the consumer, either completing or rejecting the purchase, depending on the verification results (block 84).

Thus, in accordance with the foregoing the objects of the present invention are achieved. Modifications to the present invention would be obvious to those of ordinary skill in the art, but would not bring the invention so modified beyond the scope of the appended
15 claims.

CLAIMS

What is claimed is:

1. A method of making purchases over a computer network using a first number that identifies a consumer's account from which funds will be withdrawn to pay a purchase price and a second number associated with said first number which, when used with said first number, enables withdrawal of funds from said account, said method comprising the steps of:

5 transmitting said first number over said network from a consumer location to an on-line merchant location;

forwarding said first number over said network from said on-line merchant location to a third party contractor location;

10 transmitting said second number over said network from said consumer location to said third party contractor location; and

checking at said third party contractor location whether said first and second numbers are valid.

2. The method according to claim 1 wherein said on-line merchant location is bypassed when said second number is transmitted from said consumer location to said third party contractor location.

3. The method according to claim 1 wherein said first and second numbers are transmitted over said network via encrypted connections.

4. The method according to claim 1 wherein said network is the Internet.
5. The method according to claim 1 including the additional step of checking at said third party contractor location whether said account has sufficient funds to cover said purchase price.
6. The method according to claim 1 including the additional step of transmitting a signal from said third party contractor location to said on-line merchant location indicating whether said first and second numbers are valid.
7. The method according to claim 5 including the additional step of transmitting a signal from said third party contractor location to said on-line merchant location indicating whether there are sufficient funds in said account to cover said purchase price.
8. The method according to claim 1 including the additional step of transmitting a signal from said on-line merchant location to said consumer location indicating whether said purchase has been authorized.
9. A system for making purchases over a computer network using a first number that identifies a consumer's account from which funds will be withdrawn to pay a purchase price and a second number associated with said first number which, when used with said first number, enables withdrawal of funds from said account, said system comprising:

13. The system according to claim 9 wherein said third computer checks whether said account has sufficient funds to cover said purchase price.

14. The system according to claim 9 wherein said third computer notifies said second computer whether said first and second numbers are valid.

15. The system according to claim 13 wherein said third computer notifies said second computer whether there are sufficient funds in said account to cover said purchase price.

16. The system according to claim 9 wherein said second computer notifies said first computer whether said purchase is authorized.

ABSTRACT

A method of and system for making purchases over a computer network using an ATM card or the like is provided. In accordance with the invention, a consumer transmits his ATM card number over the network to an on-line merchant. The on-line merchant then
5 forwards the ATM card number to a third party contractor, such as a bank, that will oversee and authorize the transaction. Simultaneously or thereafter, the consumer transmits his PIN over the network to the third party contractor, who verifies that the ATM card number and PIN are valid.

662060-5824660




Fig. 1




Fig. 2




Fig. 3




Fig. 4

```

import java.io.*;
import java.net.*;
import java.util.*;
import java.util.Date ;
import com.ms.com.*;
import com.ms.asp.*;

public class JRoute
{
    public Socket socSocket;
    int m_iTimeout=10000;
    J8583 msg = new J8583();

    public int init(String input)
    {

        //VAR DECLARATIONS

        int port=0,ok=0;//CONNECTION PORT,CHECKSUM

        String hostname="localhost";//DEFAULT

        DataOutputStream theOutputStream;
        int parnum=8;
        String strInput="";

        String cardNumber="",amount="",expirydate="",trannum="",tid="",mid="",unique="",goAway="";

        try{

            ////////////////////READ INI PARS
            StringTokenizer tkToken = new StringTokenizer(input);

            hostname = tkToken.nextToken();
            port = Integer.parseInt(tkToken.nextToken());
            m_iTimeout = Integer.parseInt(tkToken.nextToken());

            ////////////////////

            //CARD NEEDS TO BE SENT TO OKTOPUS
            //BUILD MSG

            msg.addField(2,cardNumber);
            msg.addField(4,amount);
            msg.addField(14,expirydate);
            msg.addField(37,"1");
            msg.addField(41,tid);
            msg.addField(42,mid);
            msg.addField(61,unique);

            //CREATE SOCKET
            try
            {
                socSocket = new Socket(hostname,port);
                socSocket.setSoTimeout(m_iTimeout);
                socSocket.setTcpNoDelay(true);
            }
            catch (UnknownHostException e)
            {
                return(-4); //HOST NOT FOUND
            }

            catch(IOException sockErr)
            {
                return(-3);
            }
        }
    }
}

```

Fig. 5(a)

```

        }
        catch(Exception all)
        {
            return(-2);
        }

        msg.sendData(socSocket);

    }
    catch(Exception er)
    {
        return(-1); //SEND ERROR
    }

    return(-1);
}

public int listenfordata()
{
    //8583 CLASS
    msg.receive(socSocket);
    try
    {
        if(msg.decide(socSocket)==0) //APPROVAL
        {
            try{
                return(0); //ITS GOOD
            }
            catch(Exception any)
            {
                return(-2); //ERROR
            }
        }
        else
        {
            return(1); //DENIED
        }
    }
    catch(Exception e)
    {
        return(-3); //ERROR
    }
}

import java.io.*;
import java.net.*;

public class J8583
{
    private byte m_baOut[] = new byte[1024]; //OUTGOING BUFFER
    private int m_baOutIndex=0; //0 BASED INDEX OF FILLED BYTES
    private DataOutputStream m_dosData;
    private BufferedInputStream m_bisInput;
    private int m_field[] = new int[30];
    private String m_value[] = new String[30];

    public J8583()
    {
        //CONSTRUCTOR
    }
    public void readFields()
    {
        int x=0;
        for(x=0;x<30;x++)
            System.out.print(m_field[x]+"="+m_value[x]+"\\n");
    }
}

```

Fig. 5(4)

```

public void addField(int field,String value)
{
    int x,j;
    j = value.length();
    m_baOut[m_baOutIndex] = (byte)field;
    m_baOutIndex++;

    for(x=0;x < j ;x++) //THE INDEX IS ONE HIGH TO LEAVE A NULL BETWEEN FIELDS
        m_baOut[x+m_baOutIndex] = (byte)value.charAt(x);

    m_baOutIndex += j+1;//RESET THE INDEX
}

public void sendData(Socket socLocal)
{
    try
    {
        //SEND
        m_dosData = new DataOutputStream(socLocal.getOutputStream());
        m_dosData.write(m_baOut,0,m_baOutIndex);
    }
    catch (UnknownHostException e)
    {
        System.out.print(e);
        System.exit(0);
    }
    catch(IOException sockErr)
    {
        System.out.print("Socket Connection: "+sockErr);
        System.exit(0);
    }
    catch(Exception all)
    {
        System.out.print("Socket Error: "+all);
        System.exit(0);
    }
}

public String resolveFieldValue(int fieldNumber)
{
    int x=0;
    for(x=0;x<30;x++)
        if(m_field[x]==fieldNumber)
            return(m_value[x]);

    return("");
}

public void receive(Socket socLocal)
{
    try
    {
        m_bisInput = new BufferedInputStream(socLocal.getInputStream());

        int k=1,index=0;
        byte buff[] = new byte[1024];
        m_bisInput.read(buff,0,1024);

        for(k=0;k<30;k++)//INITIALIZE THE NULL STRINGS
            m_value[k]="";

        k=1;

        m_field[index] = buff[index];    //FIRST FIELD MARKED BY FIRST BYTE
        while(k<1024)
        {
            if(buff[k]!=0)
            {
                m_value[index]+=(char)buff[k++];
            }
            else
            {

```

Fig. 5(c)


```

        if(buf[k+1]==0)//END OF STREAM
            break;
        else
        {
            index++;
            m_field[index] = buf[k+1];
            //      System.out.print("|"+buf[k+1]+"|");
            k+=2;
        }
    }

}

}
catch(IOException err)
{
    //TIMEOUT

    //System.out.print((nTimeout)/1000+" Second Timeout");
    try
    {socLocal.close();}
    catch(IOException Error){System.out.print("p"+Error);}

}
catch(Exception all)
{
    //MOST LIKELY A CLOSE ON IQ
    System.out.print("Network Connection Closed " + all);
    //redirect(urlTimeout);
}
}
public int decide(Socket socLocal)
{
    int k=0,index=0;
    byte pResult=0;

    for(k=0;k<30;k++)
        if(m_field[k]==39)//GRAB PIN FIELD
            pResult=(byte)m_value[k].charAt(0);

    try{socLocal.close();}
    catch(IOException e){}

    if(pResult==48)//0 IS APPROVED
    {
        //System.out.print("Thank You For Shopping At Electronic Paycheck");
        return(0);
    }
    else
    {
        //System.out.print("Denied");
        return(1);
    }
}
}
}

```

Fig. 5(a)

```

// webhostDlg.cpp : implementation file
//

#include "stdafx.h"
#include "webhost.h"
#include "webhostDlg.h"

#include <afxtempl.h> // list

#ifdef TimeOut
#define TimeOut 200
#endif

#define TimerID 0x4000

#ifdef _DEBUG
#define new DEBUG_NEW
#undef THIS_FILE
static char THIS_FILE[] = __FILE__;
#endif

////////////////////////////////////
// CAboutDlg dialog used for App About

class CAboutDlg : public CDialog
{
public:
    CAboutDlg();

// Dialog Data
   //{{AFX_DATA(CAboutDlg)
    enum { IDD = IDD_ABOUTBOX };
    }}AFX_DATA

    // ClassWizard generated virtual function overrides
   //{{AFX_VIRTUAL(CAboutDlg)
protected:
    virtual void DoDataExchange(CDataExchange* pDX); // DDX/DDV support
    }}AFX_VIRTUAL

// Implementation
protected:
   //{{AFX_MSG(CAboutDlg)
    }}AFX_MSG
    DECLARE_MESSAGE_MAP()
};

CAboutDlg::CAboutDlg() : CDialog(CAboutDlg::IDD)
{
   //{{AFX_DATA_INIT(CAboutDlg)
    }}AFX_DATA_INIT
}

void CAboutDlg::DoDataExchange(CDataExchange* pDX)
{
    CDialog::DoDataExchange(pDX);
   //{{AFX_DATA_MAP(CAboutDlg)
    }}AFX_DATA_MAP
}

BEGIN_MESSAGE_MAP(CAboutDlg, CDialog)
   //{{AFX_MSG_MAP(CAboutDlg)
    // No message handlers
    }}AFX_MSG_MAP
END_MESSAGE_MAP()

////////////////////////////////////
// CWebhostDlg dialog

CWebhostDlg::CWebhostDlg(CWnd* pParent /*=NULL*/)

```

Fig. 6(a)

```

        : CDialog(CWebhostDlg::IDD, pParent)
    {
       //{{AFX_DATA_INIT(CWebhostDlg)
        m_in = 0;
        m_out = 0;
        m_q = _T("");
       //}}AFX_DATA_INIT
        // Note that LoadIcon does not require a subsequent DestroyIcon in Win32
        m_hIcon = AfxGetApp()->LoadIcon(IDR_MAINFRAME);
    }

void CWebhostDlg::DoDataExchange(CDataExchange* pDX)
{
    CDialog::DoDataExchange(pDX);
    //{{AFX_DATA_MAP(CWebhostDlg)
    DDX_Control(pDX, IDC_LST, m_lst);
    DDX_Text(pDX, IDC_IN, m_in);
    DDX_Text(pDX, IDC_OUT, m_out);
    DDX_Text(pDX, IDC_Q, m_q);
   //}}AFX_DATA_MAP
}

BEGIN_MESSAGE_MAP(CWebhostDlg, CDialog)
    //{{AFX_MSG_MAP(CWebhostDlg)
    ON_WM_SYSCOMMAND()
    ON_WM_PAINT()
    ON_WM_QUERYDRAGICON()
    ON_WM_TIMER()
   //}}AFX_MSG_MAP
END_MESSAGE_MAP()

extern CWebhostApp theApp ;
CWebhostDlg* pDlg ;
char dbParam[256] ;

#include <ep_init.h>
#include <format.h>

#define __STDC__
#include <d3des.h>

EPsql sql ;
Listener listener ;
CList<Auth*,Auth*> Qa ;
CList<EndPoint*,EndPoint*> Qe ;
int matchF[]={ 2,14,41,42,61,0 } ; // f61=uniqueID, f44="5A315405018B44C4"
unsigned char key[]={ 0x29, 0xda, 0x91, 0x0b, 0x80, 0x9b, 0xfe, 0xd3 } ;

CString sDebug ;

void Listener::OnAccept(int nErrorCode) {
    EndPoint* tmp=new EndPoint();
    if (Accept(*tmp)) tmp->init(); else delete tmp ;
}

int EndPoint::respond() {
    const char *p ;
    char pkt[1024],*s=pkt ;
    int i,d[]={ 35,43,47,48,52,62,102,103,0 } ;
    if (getType()==0) return 0 ;
    i=0 ; while (d[i]) { set(d[i],NULL) ; i++ ; }
    for (i=2; i<128; i++)
    { if (p=get(i)) { *s=i ; strcpy(s+1,p) ; s+=strlen(p)+2 ; } }
    return Send(pkt,s-pkt) ;
}

int EndPoint::aging(int t) {
    if (t) { if (t==1) sec-- ; else sec=t ; }
    return sec ;
}

```

Fig. 6(b)

```

int EndPoint::match(M8583* m) {
    int f,i=0;
    while (f=matchF[i++]) if (strcmp(m->get(f),get(f))) return 0;
    return 1;
}

void EndPoint::init() {
    char buf[32];
    CString ip0;
    UINT port;
    BOOL nodelay=TRUE;
    SetSockOpt(TCP_NODELAY,&nodelay,sizeof(BOOL),IPPROTO_TCP);
    sec=Timeout; Qe.AddTail(this); pDlg->m_in++;
    GetPeerName(ip0,port); ip=inet_addr(ip0);
    sprintf(buf,"Connect %08x",ip); pDlg->note(buf);
}

void EndPoint::reject(int code) {
    char buf[32];
    sprintf(buf,"Reject %08x, code=%d",ip,code); pDlg->note(buf); sec=0;
    set(39,"100"); set(44,buf+16); respond();
}

void EndPoint::OnReceive(int nErrorCode) {
    Auth* a;
    EndPoint* e=NULL;
    POSITION pos1,pos2;
    BOOL fullTrans=TRUE;
    short len,l,i,f;
    const char* pp;
    char *p,pin[24],pan[20],buf[1024],scode[]="1200",offset[]="0000";
    if (nErrorCode) { sec=0; return; }
    len=Receive(buf,1020); buf[len]=0; p=buf; setType(1200); *pin=1;
    while (*p) {
        l=strlen(p); if ((*p==61)&&(l==2)&&(p[1]!='A')) fullTrans=FALSE;
        if (set(*p,p+1,8)<1) { reject(*p); return; }
        if ((*p==52)&&(l<14)) // clear PIN
            { *pin=0; pin[1]=1-1; strcpy(pin+2,p+1); memset(pin+1+1,15,10); }
        p+=(l+1); // build PIN block
    }
    if ((pp=get(52))&&(strcmp(pp,"F01",3)==0)) { reject(52); return; }
    i=0; while (f=matchF[i++]) if (get(f)==NULL) { reject(f); return; }
    if (*pin==0) { // got clear PIN, build PAN block, update PIN block
        strcpy(pan,offset); strncpy(pan+4,get(2)+strlen(get(2))-13,12);
        p=pin; for (i=0; i<16; i++) { *p=(*p^pan[i])&15; p++; }
        for (i=0; i<8; i++) pin[i]=(pin[i*2]<4)+pin[i*2+1];
        deskey(key,0); des((unsigned char*)pin,(unsigned char*)pan);
        for (i=0; i<8; i++) bin2hex(pin+i*2,pan[i]); pin[16]=0; set(52,pin);
        strcpy(buf,get(2)); strcat(buf,""); strcat(buf,get(14));
        strcat(buf,scode); strcat(buf,offset); set(35,buf);
    } // service code and offset hardcoded
    if (fullTrans) {
        pos2=Qe.GetHeadPosition();
        while (pos2) {
            pos1=pos2; e=Qe.GetNext(pos2);
            if (!match(e)||e==this) e=NULL; else { Qe.RemoveAt(pos1); break; }
        }
    }
    if (!fullTrans||fullTrans&&e)
        { a=new Auth(this,e); Qa.AddTail(a); Qe.RemoveAt(Qe.Find(this)); }
    sprintf(buf,"Recv %08x %d, card=%s",ip,len,get(2)); pDlg->note(buf);
}

Auth::Auth(EndPoint* e1, EndPoint* e2) {
    int i;
    const char* p;
    char f[16],dest[4]="N?";
    e[0]=e1; e[1]=e2; cp(*e1);
    if (e2) {

```

Fig. 6(c)

```

        if (e2->getType()==1200) setType(1200); set(3,"000000");
        for (i=2; i<128; i++) if (p=e2->get(i)) set(i,p);
    } else { set(3,"300000"); set(4,"000000000000"); }
    if (fillMsg(*this,sql,dbParam,3)) // 1: BIN, 2: mid/tid
    { e1->reject(1); if (e2) e2->reject(1); setType(0); return; }
    id=++pDlg->m_out; pDlg->UpdateData(FALSE);
    set(37,itoa(id,f,10),8); pDlg->m_ep.cp(*this);
    dest[1]=*(get(47)+1); pDlg->m_ep.send(dest);
}

BOOL Auth::isActive() {
    if ((e[1]==NULL)||((e[0]->aging(0)>0)&&(e[1]->aging(0)>0)) return TRUE;
    setType(0); return FALSE;
}

Auth::~Auth() {
    for (int i=0; i<2; i++) if (e[i])
    { e[i]->cp(*this); e[i]->respond(); delete e[i]; }
    setType(0);
}

////////////////////////////////////
// CWebhostDlg message handlers

BOOL CWebhostDlg::OnInitDialog()
{
    CDialog::OnInitDialog();

    // Add "About..." menu item to system menu.

    // IDM_ABOUTBOX must be in the system command range.
    ASSERT((IDM_ABOUTBOX & 0xFFF0) == IDM_ABOUTBOX);
    ASSERT(IDM_ABOUTBOX < 0xF000);

    CMenu* pSysMenu = GetSystemMenu(FALSE);
    if (pSysMenu != NULL)
    {
        CString strAboutMenu;
        strAboutMenu.LoadString(IDS_ABOUTBOX);
        if (!strAboutMenu.IsEmpty())
        {
            pSysMenu->AppendMenu(MF_SEPARATOR);
            pSysMenu->AppendMenu(MF_STRING, IDM_ABOUTBOX, strAboutMenu);
        }
    }

    // Set the icon for this dialog. The framework does this automatically
    // when the application's main window is not a dialog
    SetIcon(m_hIcon, TRUE);           // Set big icon
    SetIcon(m_hIcon, FALSE);        // Set small icon

    // TODO: Add extra initialization here
    char IP[256],name[4],title[16];
    short TCPPort,port;
    const char fmt[]="%s %hd %2s %s %hd %s";
    const char usage[]="Usage: webhost IP port name DBparam listenPort";
    if (sscanf(theApp.m_lpCmdLine,fmt,IP,&TCPPort,name,dbParam,&port)<5)
    { ::MessageBox(NULL,usage,"Error",MB_OK); EndDialog(0); return FALSE; }
    sprintf(title,"WebHost %s %d",name,port); SetWindowText(title);
    if (!listener.Create(port)) {
        ::MessageBox(NULL,"Unable to create TCP/IP sockets.", "Error",MB_OK);
        EndDialog(0); return FALSE;
    }
    if (!listener.Listen()) {
        ::MessageBox(NULL,"Network error.", "Error",MB_OK);
        EndDialog(0); return FALSE;
    }
    if (m_ep.connect(IP,TCPPort,name)) {
        ::MessageBox(NULL,"Error connecting to EProute.", "Error",MB_OK);
        EndDialog(0); return FALSE;
    }
}

```

Fig. 6(a)

```

    }
    pDlg=this ; SetTimer(TimerID,1000,NULL) ;
        return TRUE; // return TRUE unless you set the focus to a control
    }

void CWebhostDlg::OnSysCommand(UINT nID, LPARAM lParam)
{
    if ((nID & 0xFFF0) == IDM_ABOUTBOX)
    {
        CAboutDlg dlgAbout;
        dlgAbout.DoModal();
    }
    else
    {
        CDialog::OnSysCommand(nID, lParam);
    }
}

// If you add a minimize button to your dialog, you will need the code below
// to draw the icon. For MFC applications using the document/view model,
// this is automatically done for you by the framework.

void CWebhostDlg::OnPaint()
{
    if (IsIconic())
    {
        CPaintDC dc(this); // device context for painting

        SendMessage(WM_ICONERASEBKGND, (LPARAM) dc.GetSafeHdc(), 0);

        // Center icon in client rectangle
        int cxIcon = GetSystemMetrics(SM_CXICON);
        int cyIcon = GetSystemMetrics(SM_CYICON);
        CRect rect;
        GetClientRect(&rect);
        int x = (rect.Width() - cxIcon + 1) / 2;
        int y = (rect.Height() - cyIcon + 1) / 2;

        // Draw the icon
        dc.DrawIcon(x, y, m_hIcon);
    }
    else
    {
        CDialog::OnPaint();
    }
}

// The system calls this to obtain the cursor to display while the user drags
// the minimized window.
HCURSOR CWebhostDlg::OnQueryDragIcon()
{
    return (HCURSOR) m_hIcon;
}

void CWebhostDlg::OnTimer(UINT nIDEvent)
{
    // TODO: Add your message handler code here and/or call default
    Auth* a ;
    EndPoint* e ;
    POSITION pos1,pos2 ;
    BOOL del=FALSE ;
    if (nIDEvent==TimerID) {
        pos2=Qe.GetHeadPosition() ;
        while (pos2) {
            pos1=pos2 ; e=Qe.GetNext(pos2) ;
            if (e->aging()<1) { Qe.RemoveAt(pos1) ; del=TRUE ; delete e ; }
        }
        pos2=Qa.GetHeadPosition() ;
        while (pos2) {
            pos1=pos2 ; a=Qa.GetNext(pos2) ;

```

Fig. 6 (e)

```

        if (!a->isActive()) { Qa.RemoveAt(pos1); del=TRUE; delete a; }
    }
    if (del) note(NULL);
}
    CDialog::OnTimer(nIDEvent);
}

void CWebhostDlg::note(const char* s) {
    if (s)
    { m_lst.AddString(s); if (m_lst.GetCount()>14) m_lst.DeleteString(0); }
    m_q.Format("%d %d",Qe.GetCount(),Qa.GetCount()); UpdateData(FALSE);
}

void On8583(short mType, EPacket* ep) {
    int n,i;
    char s[64];
    const char* p;
    POSITION pos1,pos2;
    Auth* a;
    if ((mType==-1)||ep->mustExit()) { pDlg->EndDialog(0); return; }
    if (mType) return; // ignore other administrative messages
    ep->receive(); if (ep->getType()==1430) return;
    if (p=ep->get(37)) n=atoi(p); else return;
    pos2=Qa.GetHeadPosition();
    while (pos2) {
        pos1=pos2; a=Qa.GetNext(pos2);
        if (a->match(n)) {
            ep->set(37,NULL); for (i=2; i<128; i++) if (p=ep->get(i)) a->set(i,p);
            Qa.RemoveAt(pos1); delete a; pDlg->note(NULL); return;
        }
    }
    pDlg->note("reversal"); ep->getType(s); memset(s+4,'0',18); s[22]=0;
    if (p=ep->get(11)) strncpy(s+4,p,6);
    if (p=ep->get(12)) strncpy(s+10,p,12);
    if (p=ep->get(32)) strcpy(s+22,p);
    ep->set(56,s); ep->setType(1420); ep->send(ep->getSender());
}
/*
sDebug.Format("");
::MessageBox(NULL,sDebug,"Debug",MB_OK);
*/

```

Fig. 6(f)

Please type a plus sign (+) inside this box → ☒

PTO/SB/01 (12-97)

Approved for use through 9/30/00. OMB 0651-0032

Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

**DECLARATION FOR UTILITY OR
DESIGN
PATENT APPLICATION
(37 CFR 1.63)**

Attorney Docket Number	5932.1
First Named Inventor	Douglas W. King
COMPLETE IF KNOWN	
Application Number	/
Filing Date	
Group Art Unit	
Examiner Name	

☒ Declaration Submitted with Initial Filing **OR** ☐ Declaration Submitted after Initial Filing (surcharge (37 CFR 1.16 (e)) required)

As a below named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

Method of and system for making purchases over a computer network

the specification of which (Title of the Invention)

☒ is attached hereto

OR

☐ was filed on (MM/DD/YYYY) as United States Application Number or PCT International

Application Number and was amended on (MM/DD/YYYY) (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached?	
				YES	NO
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

☐ Additional foreign application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto:

I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) listed below.

Application Number(s)	Filing Date (MM/DD/YYYY)	<input type="checkbox"/> Additional provisional application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

[Page 1 of 2]

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

EL317433794US

Please type a plus sign (+) inside this box → ☒

PTO/SB/01 (12-97)
Approved for use through 9/30/00. OMB 0651-0032

Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION — Utility or Design Patent Application

I hereby claim the benefit under 35 U.S.C. 120 of any United States application(s), or 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

U.S. Parent Application or PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)

☐ Additional U.S. or PCT international application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

As a named inventor, I hereby appoint the following registered practitioner(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith: ☐ Customer Number OR

☒ Registered practitioner(s) name/registration number listed below

Place Customer
Number Bar Code
Label here


Name	Registration Number	Name	Registration Number
James E. Marina, Esq.	41,969		

☐ Additional registered practitioner(s) named on supplemental Registered Practitioner Information sheet PTO/SB/02C attached hereto.

Direct all correspondence to: ☐ Customer Number OR ☒ Correspondence address below

Name	James E. Marina, Esq.				
Address	Winston & Strawn				
Address	200 Park Avenue				
City	New York	State	NY	ZIP	10166
Country	U.S.A.	Telephone	212-294-6700	Fax	212-294-4700

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Name of Sole or First Inventor:		<input type="checkbox"/> A petition has been filed for this unsigned inventor			
Given Name (first and middle (if any))		Family Name or Surname			
Douglas W.		King			
Inventor's Signature				Date	9-3-99
Residence: City	Santa Maria	State	CA	Country	U.S.A.
Post Office Address					
Post Office Address	4485 Hill Court				
City	Santa Maria	State	CA	ZIP	93454
				Country	U.S.A.

☐ Additional inventors are being named on the supplemental Additional Inventor(s) sheet(s) PTO/SB/02A attached hereto